



RoadRun TexRough SR



- *32 kHz sensor aimed at high speed texture measurements*
- *Plug and Play sensor compatible with existing systems*

Technical Specifications

RoadRun TexRough SR

- 32 kHz sensor aimed at high speed texture measurements
- Plug and Play sensor compatible with existing systems

Measurement Range:	(MR)	200 mm
Stand-Off distance:	(SO)	200 mm
Resolution:		0,05 mm
Sampling Speed:		32 kHz
Interfaces:	RS422 – Clock / Data (resolution = R/4000) Service Interface	
Dimensions:	(x, y, z)	6.38 x 1.65 x 4.25 in
Weight:		2.2 Lbs
Power Supply:		+24 VDC (18-32 VDC)



LIMAB North America Inc

9301 Monroe Road, Suite B
Charlotte, NC 28270
Phone: +1 -(704) 321-0760
Fax: +1-(704) 321-0761
sales@limab.com
www.limab.com

LIMAB AB

Exportgatan 38 B
422 46 Hisings Backa (Gothenburg)
Sweden
Phone: +46 (0)31 58 44 00
Fax: +46 (0)31 58 33 88
sales@limab.se
www.limab.com

LIMAB OY

Henry Fordin katu 5K
FIN 00150 HELSINKI
Phone: +358 947 80 36 68
Fax: +358 947 80 36 67
Pekka.haimi@limab.fi
www.limab.fi

LIMAB UK Ltd

Unit 1J Chelston Enterprise Centre
Castle Road, Wellington, England
Phone: +44 (0)1823 668633
Fax: +44 (0)1823 652625
sales@limab.co.uk
www.limab.co.uk

LIMAB GmbH

Mitterlängstrasse 28
D-82178 PUCHHEIM
Phone: +49 (0)89-84 05 83 20
Fax: +49 (0)89-84 05 83 21
michael.karlsson@limab.de
www.limab.de