

MIKRON IRC 35 TO IRC 150

Calibration source with a single fixed temperature for inspection of pyrometers. Temperatures ranging from 35 to 150°C (95 to 302°F).



AT A GLANCE

The Mikron® calibration sources of type IRC 35 to IRC 150 are instruments for inspection of the measurement accuracy of pyrometers (radiation thermometers) at a fixed temperature value. The highly accurate control ensures a constant and stable heating of the large emitter surface with a high temperature uniformity with a maximum deviation of 0.2°C. The robust stainless steel design guarantees the operation even under rough industrial environments. The compact dimensions also allows for verifying fixed installed pyrometers at the measuring location.

PRODUCT HIGHLIGHTS

- Ten different types for fixed adjusted temperatures of 35°C, 45°C, 70°C, 75°C, 95°C, 100°C, 110°C, 120°C, 140°C, or 150°C
- High emissivity: 98%
- Large aperture diameter: 50.8 mm (2")
- Short warm-up time
- High temperature stability
- Small dimensions
- Stainless steel housing

TYPICAL APPLICATIONS

- Single point temperature calibrations of point IR pyrometers
- Fixed mount and portable pyrometer calibration verification

Fixed Temperatures

35°C, 45°C, 70°C, 75°C, 95°C, 100°C, 110°C, 120°C, 140°C, or 150°C

Measurement Uncertainty

IRC 35

0.4°C for $T_U = 10$ to 30°C

IRC 45 to IRC 120

0.4°C for $T_U = 10$ to 40°C

0.6°C for $T_U = 0$ to 10°C

IRC 140 to IRC 150

0.5°C for $T_U = 10$ to 40°C

0.7°C for $T_U = 0$ to 10°C

Emissivity

0.98 ± 0.004 (for $\lambda = 2$ to 5.4 μm
 $\lambda = 8$ to 14 μm)

Aperture Diameter

50.8 mm (2")

Warm-up Time

max. 5 (IRC 35) to 30 min (IRC 150)

TECHNICAL DATA

Measurement Specifications		
Fixed Temperature (dependent on type)	35°C (95°F), 45°C (113°F), 70°C (158°F), 75°C (167°F), 95°C (203°F), 100°C (212°F), 110°C (230°F), 120°C (248°F), 140°C (284°F), or 150°C (302°F)	
Temperature Uncertainty	IRC 35	0.4°C for T _U = 10 to 30°C
	IRC 45 to IRC 120	0.4°C for T _U = 10 to 40°C
		0.6°C for T _U = 0 to 10°C
	IRC 140 to IRC 150	0.5°C for T _U = 10 to 40°C
0.7°C for T _U = 0 to 10°C		
Stability	0.1°C	
Temperature Uniformity	0.2°C (central area Ø 45 mm)	
Emissivity ε	0.98 ±0.004 (for λ = 2 to 5.4 μm λ = 8 to 14 μm)	
Aperture Diameter	50.8 mm (2")	
Repeatability	0.2°C	
Warm-up Time	max 5 (IRC 35) to 30 min (IRC 150)	

Environmental and Electrical Specifications		
Operating Temperature	IRC 35	0 to 30°C (32 to 86°F)
	IRC 45 to IRC 150	0 to 40°C (32 to 104°F), temporary (2 min) up to 70°C (158°F)
Storage Temperature	0 to 70°C (32 to 158°F)	
Relative Humidity	10 to 85%, non-condensing conditions	
Status LED:	Green: warm-up	
	Orange: ready for operation	
	Red: overheating	
Protection Class	IP50 (EN 60529)	
Dimensions (Ø x D x H)	64.5 mm x 81.0 mm x 133.5 mm (~2.54" x 3.19" x 5.26")	
Weight	0.85 kg (~1.88 lbs)	
Power Supply	24 V DC, max 1 A	
CE Certified	According to EU directives about electromagnetic immunity	

REFERENCE NUMBERS

PN	Description
43001-10350	Calibration source IRC 35
3 891 130	Calibration source IRC 45
3 891 140	Calibration source IRC 70
3 891 150	Calibration source IRC 75
3 891 160	Calibration source IRC 95
3 891 170	Calibration source IRC 100
3 891 180	Calibration source IRC 110
3 891 410	Calibration source IRC 120
3 891 190	Calibration source IRC 140
3 891 200	Calibration source IRC 150

Scope of Delivery

Calibration source, stand, power supply 230 VAC ⇒ 24 VDC, user manual, works certificate

ACCESSORIES

PN	Description
3 890 420	Plastic carrying bag



For international contact information,
visit advancedenergy.com.

sales.support@aei.com
+1 970 221 0108

ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than three decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

AE's power solutions enable customer innovation in complex semiconductor and industrial thin film plasma manufacturing processes, demanding high and low voltage applications, and temperature-critical thermal processes.

With deep applications know-how and responsive service and support across the globe, AE builds collaborative partnerships to meet rapid technological developments, propel growth for its customers and power the future of technology.

PRECISION | POWER | PERFORMANCE

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2020 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, Mikron®, and AE® are U.S. trademarks of Advanced Energy Industries, Inc.

